



R45305B

Digital LED calendar clock with flush mounting case

- + Double-line display of weekday, day, month, hours, minutes and seconds
- + 12 or 24 hours mode
- + Modes of operation:
 - + Stand-alone quartz clock
 - + Slave clock synchronised by polarised 24 V DC minute impulses of a master clock
 - + Self-correcting slave clock synchronised by 24 V DC time code of a BMC/MPU-TC master clock
 - + Synchronisation via w482 time code signal from a series HUR master clock
 - + Synchronisation directly from DCF- or GPS-receiver
- + Red bright LED dot-matrix display with 50 mm digit height
- + Readability up to 25 m
- + Data storage up to 3 days in case of mains failure
- + with separate steel mounting box for solid wall
- + Including IR handset for configuration and multifunction stopwatch operation

Technical specifications:

Case:	Aluminium, rectangular flush mounting case with steel box
Accuracy:	±0.1 sec./day (at 20..25 °C)
Power supply:	220..240 V AC / 50 Hz
Ambient temperature:	0..45 °C
Dimensions (WxHxD):	Steel box 486 x 186 x 80 mm Front panel 492 x 192 x 3 mm
Weight:	approx. 3 kg

Options:

R4-DCF:	DCF-77 radio synchronisation antenna
R4-TEMP:	External temperature sensor

